

Short Form Classification Report No. 18911F

PRODUCT

PV16-300, PV16-270, PV16-260P, PV16-270P, PV16-280

SPONSOR

Viridian Solar

PRODUCT DETAILS & FIELD OF APPLICATION (SUMMARY)

- Thickness: 69 mm
- Weight one solar panel: 21 kg
- Dimensions: 992 x 1640 mm x mm
- Use of fire retardants: No

- Range of pitches: > 10°
- Range of decks:
Supporting timbers (47 x 70 mm) + PE vapour barrier (0,4mm) + Wooden battens (25 x 50 mm) +
Non-combustible roof tiles (A1 according to EN 13501-1)

See the annex on page 2 for a fully detailed field of application and product details.

CLASSIFICATION

BROOF (t4)

STANDARDS

Test standard: CEN/TS 1187:2012: Test 4 & CEN/TS 16459:2013

Classification standard: EN 13501 5:2016

SIGNED

APPROVED

For and on behalf of WFRGENT nv

This short form classification report has been drafted according to EGOLF agreement EGA 08rev2:2013 "Application note: clause 5.10 [5.10/1] – Types of test reports used in fire testing". Whilst the test data and classification provided within this short form report was obtained in a test conducted fully in accordance with the standards CEN/TS 1187:2012:Test 4 & CEN/TS 16459:2013, the presentation of the results in this short form report may not satisfy the requirements of those standards and EN ISO/IEC 17025:2005/AC:2006 & EN 13501 5:2016. The presentation of the results in this manner is made by agreement with the sponsor and use of the information herein for product assessment, approval or certification purposes will be restricted.

The full classification report No. **18911C** is available at **Viridian Solar**.

This document is the original version of this report and is written in English. This document may be used only literally and completely for publications. For publications of certain texts, in which this document is mentioned, our permission must be obtained in advance.

The authenticity of the electronic signatures is assured by Belgium Root CA.

Annex – fully detailed field of application and product details

PRODUCT DETAILS

Mechanical and Electrical specifications						
Model	PV16-	260P	270	270P	280	300
Thickness	mm	69				
Weight one solar panel	kg	21				
Dimensions	mm x mm	992 x 1640				
Peak Power	Wp	260	270	270	280	300
Module Efficiency	%	16,6	17,3	17,3	17,9	19,2
Number of cells		60	60	60	60	60
Cell Type (-crystalline silicon)		Poly-	Mono-	Poly-	Mono-	Mono-

FIELD OF APPLICATION

Direct field of application

- Range of pitches: > 10°

Extended field of application

➤ Layer 0: Integrated solar panel

Range of panels:	- PV16-260P - PV16-270 - PV16-300	PV16-270P PV16-280
Facing:	Low-iron glass	
Backing	PV Backsheet	
Thickness:	69 mm	
Weight of 1 solar panel:	21 kg	
Dimensions:	1640 x 992 mm	
Direction:	Portrait or landscape	
Fixation:	Mechanically fixed and installed with the respective flashings	

➤ Layer 1: Non-combustible roof tiles

Range of products:	Any non-combustible tile (A1 according to EN 13501-1)
--------------------	---

➤ Layer 2: Wooden battens

Dimensions:	25 x 50 mm
Density:	472 kg/m ³

➤ Layer 3: PE vapour barrier

Thickness:	0,4 mm
Surface weight:	121 g/m ²
Fixation:	Mechanically fixed onto the wooden battens every ± 40 cm
Reaction to fire according to EN13501-1:	E,d2

➤ Layer 4: Supporting timbers

Dimensions:	47 x 70 mm
Density:	437 kg/m ³